

WL2

Dynamic White Linear Flood Lights are suitable for scenarios such as bridges, ancient building facades, and stadiums. They deliver delicate and uniform lighting, creating an immersive effect akin to flowing water washing over walls. Supporting linear color temperature adjustment from 1800K to 6500K and sectional dimming control, they allow flexible color temperature gradients and zoned lighting combinations. The constant power function ensures consistent brightness by maintaining rated power output across the full color temperature range. With a lightweight design for easy installation, IP67-rated waterproofing, and reliable heat dissipation, these lights not only meet the atmospheric needs of venue performances but are also ideal for long-term architectural decorative lighting, infusing spaces with dynamic light and shadow.




TECHNICAL PARAMETER


Max. Power: 60W
Light source: 1800K-6500K
Luminous Flux: 6015lm
Peak Intensity: 22729cd(15°)
CRI: Ra: 90
Con Personality: DMX512, RDM

Operating voltage: AC220V-50/60Hz
Working Temperature: -20°C~45°C
Protection Level: IP67
Dimensions (L*W*H): 610*66*61mm
weight: 2.2kg

ANGLE



DIMENSIONAL DRAWING



SPECIFICATIONS



OPTIONAL ACCESSORIES




Data & Power Box (AM710)



End Termination Cap (6813100052)


LIGHT DISTRIBUTION DIAGRAM

(* THE ABOVE COLOR TEMPERATURES ARE ACHIEVED BY YAJIANG DIGITAL COLOR TECHNOLOGY AND CCS TECHNOLOGY)




ALL BRIGHT

Lumen 5158lm
 Illuminance 825lx(5m)
 Peak Intensity 20729cd(15°)



COLD WHITE

Lumen 6015lm
 Illuminance 905lx(5m)
 Peak Intensity 22729cd(15°)



WARM WHITE

Lumen 4989lm
 Illuminance 767lx(5m)
 Peak Intensity 19272cd(15°)

ILLUMINANCE AT DISTANCE

