

The user-friendly control terminal features a minimalist design suitable for various commercial spaces. Its responsive touch interface allows for seamless color mode switching and brightness adjustment, enabling users to evoke positive emotions without the need for professional expertise. Deeply integrated with the full series of devices, it supports one-touch control of either localized or overall lighting—instantly adapting to scenarios such as bar ambiance transitions or meeting room mode adjustments—making the operation of emotional lighting more intuitive and accessible.



MAIN FUNCTION	TECHNICAL PARAMETER																
86 type Intelligent Panel, easy for wall mounting - Capacitive multi-function touch LCD color display - Built-in WSP32S3 chip, wireless connection, or directly connected to the server - One-click linkage multi-area control, including single scene control and grouped scenes - The protocol supports user-defined names and supports a maximum of 16 scenes - The Intelligent Panel can be controlled independently for a single area or multiple areas - Single-area control: Use the server backstage to perform a single-area - Multi-area linkage control: Each cross-area scenes can be added to multiple single-area scenes	Aura Wall Panel S <table><tr><td>Voltage</td><td>AC100-240V</td></tr><tr><td>Max.Power</td><td>1W</td></tr><tr><td>Size</td><td>86*86*29mm</td></tr><tr><td>Weight</td><td>0.1kg</td></tr><tr><td>Casing</td><td>Aero-aluminium alloy</td></tr><tr><td>Ambient Temp</td><td>-5°C ~ +45°C</td></tr><tr><td>IP Rating</td><td>IP20</td></tr><tr><td>Certification</td><td>CE</td></tr></table>	Voltage	AC100-240V	Max.Power	1W	Size	86*86*29mm	Weight	0.1kg	Casing	Aero-aluminium alloy	Ambient Temp	-5°C ~ +45°C	IP Rating	IP20	Certification	CE
Voltage	AC100-240V																
Max.Power	1W																
Size	86*86*29mm																
Weight	0.1kg																
Casing	Aero-aluminium alloy																
Ambient Temp	-5°C ~ +45°C																
IP Rating	IP20																
Certification	CE																
MAIN FUNCTION	TECHNICAL PARAMETER																
2*86 type Intelligent Panel, easy for wall mounting - Capacitive multi-function touch LCD color display - Built-in WSP32S3 chip, wireless connection, or directly connected to the server - One-click linkage multi-area control, including single scene control and grouped scenes - The protocol supports user-defined names and supports a maximum of 32 scenes - The Intelligent Panel can be controlled independently for a single area or multiple areas - Single-area control: Use the server backstage to perform a single-area - Multi-area linkage control: Each cross-area scenes can be added to multiple single-area scenes	Aura Wall Panel M <table><tr><td>Voltage</td><td>AC100-240V</td></tr><tr><td>Max.Power</td><td>1W</td></tr><tr><td>Size</td><td>176.5*118.5*34mm</td></tr><tr><td>Weight</td><td>0.1kg</td></tr><tr><td>Casing</td><td>Aero-aluminium alloy</td></tr><tr><td>Ambient Temp</td><td>-5°C ~ +45°C</td></tr><tr><td>IP Rating</td><td>IP20</td></tr><tr><td>Certification</td><td>CE</td></tr></table>	Voltage	AC100-240V	Max.Power	1W	Size	176.5*118.5*34mm	Weight	0.1kg	Casing	Aero-aluminium alloy	Ambient Temp	-5°C ~ +45°C	IP Rating	IP20	Certification	CE
Voltage	AC100-240V																
Max.Power	1W																
Size	176.5*118.5*34mm																
Weight	0.1kg																
Casing	Aero-aluminium alloy																
Ambient Temp	-5°C ~ +45°C																
IP Rating	IP20																
Certification	CE																



A. 5 SYSTEM COLOR PRODUCT

Featuring high CRI and high illumination, those products allow each scene to be controlled separately and across different regions. They are suitable for both daily white lighting and atmospheric color lighting scenes

Appearance	Product name	Installation Method
	Aura Cylinder 8	Recessed Installation φ48mm
	Aura Cylinder 20	Recessed Installation φ145mm
	Aura Cylinder 40	Recessed Installation φ145mm
	Aura Cylinder 60	Hanging installation 115x115x221.7mm
	Aura Cylinder 80	Hanging installation 115x115x285.5mm
	Aura Linear 3	Concealed Installation 292x47x50mm
	Aura Linear 6	Concealed Installation 598x47x50mm