



The core lighting device with full power range coverage features an RGBW four-color configuration paired with a high-performance color algorithm, vividly presenting "dopamine colors." Aura Cylinder 8 is ideal for accent lighting, Aura Cylinder 20/Aura Cylinder 40 suit conventional spaces such as meeting rooms, while Aura Cylinder 60/Aura Cylinder 80 meet the needs of high-ceiling halls. Powered via CAT6 Ethernet cables for safe and easy maintenance, it offers tens of millions of dimming levels for smooth brightness transitions, blending practicality with emotional appeal.


MAIN FUNCTION

- Light source RGBW
- CRI Ra:90
- Luminous flux 2956lm
- Angle 25°/45°/60° (Optional)
- Adjusting CCS intelligent color management system
- Installation method Hanging installation


TECHNICAL PARAMETER

Aura Cylinder 60	
Voltage	DC55V
Max.Power	60W
Size	115*115*221.7mm
Weight	1.62KG
Casing	Die-casting aluminum
Ambient Temp	0°C ~ +45°C
IP Rating	IP20
Certification	CE
Control	Network/RDM control, the software can be updated through the AD9191 Control Box via a web server. There are 2 RJ45 ports (DC55V power and network communication integrated into the Ethernet cable for input & output of communication.), with a maximum connection capability of 100W. The efficient distance from the Control Box to the Aura Cylinder 60 is 80meters.


14 PRESET CCT COLOR




24 PRESET COLORS




DIMENSIONS



OPTIONAL



Light shield244012665 (white)



bracket244011006 (white)

PHOTOMETRIC DATA

